









COLORI

-  5500K
-  4000K
-  3000K
-  2700K
-  Ambra
-  Rossa
-  Verde
-  Blu

-  RGB
-  AWB
-  AWWW

**3000K - CRI>90 Su richiesta

FINITURE

- Grigio 
- Nero 



CODICE: AV01003GN

IP67



Cavo 150 cm incluso
SUB4 FROST-UV 2x0,50



Potenza:
3W / 6W / 9W (RGB)



450Lm
(3000K-500mA)



Collegare in serie:
350mA / 500mA / 700mA(RGB)




CRI
>80



280
gr



OTTICHE



10° 25° 40° 60° 110°



Diff.

EMISSIONE LUMINOSA / DIAGRAMMA CONICO

0,5	0,18	E (0°) 10739 E (C0) 10,2° 5181
1,0	0,36	E (0°) 2685 E (C0) 10,2° 1295
1,5	0,54	E (0°) 1193 E (C0) 10,2° 576
2,0	0,72	E (0°) 671 E (C0) 10,2° 324
2,5	0,90	E (0°) 430 E (C0) 10,2° 207
3,0	1,1	E (0°) 298 E (C0) 10,2° 144
Distanza (m)	Diametro Cono (m)	Illuminamento (lx)
— C0 - C180 (Angolo di dimezzamento: 20,4°)		

DIMENSIONI

