

COLORI

- 5500K
- 4000K
- 3000K
- 2700K
- Ambra
- Rossa
- Verde
- Blu

- RGB
- AWB
- AWWW

1170Lm (rgb,700mA)

**3000K - CRI>90 Su richiesta

FINITURE

- Grigio
- Nero



CODICE: AV01006GN

IP67



Cavo 150 cm incluso
SUB4 FROST-UV 2x0,50



Potenza:
9W / 18W / 27W(RGB)



1350Lm
(3000K-500mA)



Collegare in serie:
350mA / 500mA / 700mA(RGB)



CRI
>80



850
gr



OTTICHE



10° 25° 40° 60° 110°



Diff.

EMISSIONE LUMINOSA / DIAGRAMMA CONICO

0,5	0,17	E (0°)	30637
		E (C0) 9,6°	14972
1,0	0,34	E (0°)	7659
		E (C0) 9,6°	3743
1,5	0,51	E (0°)	3404
		E (C0) 9,6°	1664
2,0	0,68	E (0°)	1915
		E (C0) 9,6°	936
2,5	0,85	E (0°)	1225
		E (C0) 9,6°	599
3,0	1,0	E (0°)	851
		E (C0) 9,6°	416
Distanza (m)	Diametro Cono (m)	Illuminamento (lx)	
— C0 - C180 (Angolo di dimezzamento: 19,2°)			

DIMENSIONI

