

**WIRE  
SPECIFICATION**

SPEC NO.	2 芯*20AWG	REFERENCE STANDARD	RoHS
RATED TEMPERATURE	200℃	RATED VOLTAGE	300/500V
FLAME RETARDANT GRADE	FT-2	ENVIRONMENTAL STANDARDS	RoHS

**CONSTRUCTION ITEM**

<b>CONDUCTOR</b>	SECTIONAL AREA	mm	21Φ0.18±0.008
	MATERIAL	.....	-
	SECTIONAL AREA	mm <sup>2</sup>	0.53
	STRANDED DIAMETER	mm	0.95±0.08
<b>INSULATION</b>	MATERIAL	.....	-
	THE AVERAGE THICKNESS	mm	0.42
	MINIMUM GAUGE	mm	0.38
	COLOR	.....	-
	INSULATION DIAMETER	mm	1.8±0.10
<b>SHIELDING</b>	COVERING	.....	-
	SCREEN MODE	.....	/
	SECTIONAL AREA	AWG/ mm	/
	MATERIAL	.....	/
	TOTAL DIAMETER	mm	3.6±0.20
<b>JACKET</b>	MATERIAL	.....	-
	THE AVERAGE THICKNESS	mm	1.00
	MINIMUM GAUGE	mm	0.85
	COLOR	.....	-
	OVERALL DIAMETER	mm	5.3—5.7mm

**PRINTING CONTENT**

20AWG\*2C 200℃ 300/500V SILICONE RUBBER

**STRUCTURE DIAGRAM**

