


STRIP LED DIGITALI SMD5050

5 metri



CODICE	PARAMETRI BASE						PARAMETRI FOTOMETRICI				
	Misure	Biadesivo	Input Volt	Watt nominali	Chip di controllo	Step LED	CRI	Colore Luce	LED/m - Totali	Classe Energetica	IP
AV2884XIAA	5000x10mm	3M	12VDC	12W/m	WS2811	1 : 3	-	RGB	60 - 300	A+	IP20
AV2886XIAA	5000x10mm	3M	5VDC	7,2W/m	WS2812B	1 : 1	-	RGB	30 - 150	A+	IP20
AV2888XIAA	5000x10mm	3M	5VDC	14,4W/m	WS2812B	1 : 1	-	RGB	60 - 300	A+	IP20
AV2885XIAA	5000x10mm	3M	12VDC	14,4W/m	WS2811	1 : 3	-	RGB	60 - 300	A+	IP65
AV2887XIAA	5000x10mm	3M	5VDC	7,2W/m	WS2812B	1 : 1	-	RGB	30 - 150	A+	IP65
AV2889XIAA	5000x10mm	3M	5VDC	14,4W/m	WS2812B	1 : 1	-	RGB	60 - 300	A+	IP65

I dati sopra riportati sono il risultato del test di una striscia da 1m senza processo di protezione IP. Il processo di protezione IP porta modifiche alle dimensioni, temperatura luce K e flusso luminoso.

