



# STRIP LED DIGITALI SMD5050

## 5 metri



### CODICE      PARAMETRI BASE

	Misure	Biadesivo	Input Volt	Watt nominali	
AV2886XIAA	5000x10mm	3M	5VDC	7,2W/m	WS2812B
AV2888XIAA	5000x10mm	3M	5VDC	14,4W/m	WS2811
AV2887XIAA	5000x10mm	3M	5VDC	7,2W/m	WS2812B
AV2889XIAA	5000x10mm	3M	5VDC	14,4W/m	WS2811
AV2884XIAA	5000x10mm	3M	12VDC	14,4W/m	WS2811
AV2885XIAA	5000x10mm	3M	12VDC	14,4W/m	WS2811

### PARAMETRI FOTOMETRICI

CRI	Colore Luce	Lumen nominali	Lumen effettivi	Classe Energetica	IP
-	RGB	3000LM	3 ANNI	A+	IP20
-	RGB	6000LM	3 ANNI	A+	IP20
-	RGB	3000LM	3 ANNI	A+	IP65
-	RGB	6000LM	3 ANNI	A+	IP65
-	RGB	6000LM	3 ANNI	A+	IP20
-	RGB	6000LM	3 ANNI	A+	IP65

I dati sopra riportati sono il risultato del test di una striscia da 1m senza processo di protezione IP. Il processo di protezione IP porta modifiche alle dimensioni, colore luce K e flusso luminoso.

