
PHILIPS AV6063WSAA



AV6063WSAA

4.9-50W GU10 930 36D

Delivering a warm, halogen-like accent beam, MASTER VALUE LEDspot MV is a perfect for spot lighting. Thanks to its high CRI, it realizes more natural colors, enabling cozy and comfortable ambience for residential, hospitality and emphasize the beauty of merchandise in retail. These LEDspots have the familiar look and feel of glass spots, keeping the classic beauty of glass spots and adding the strong performance from LED technology. The dimming function enables to create the desired atmosphere and it works with broad selection of dimmers.

Product data

General Information	
Cap-Base	GU10 [GU10]
Nominal Lifetime (Nom)	25000 h
Switching Cycle	50000X
Technical Type	4.9-50W
Light Technical	
Color Code	930 [CCT of 3000K]
Beam Angle (Nom)	36 °
Luminous Flux (Nom)	365 lm
Luminous Flux (Rated) (Nom)	365 lm
Luminous Intensity (Nom)	650 cd
Color Designation	White (WH)
Rated Beam Angle	36 °
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	82.65 lm/W

Color Consistency	<6
Color Rendering Index (Nom)	90
LLMF At End Of Nominal Lifetime (Nom)	70 %
Luminous Flux In 90° Cone (Rated)	365 lm
Operating and Electrical	
Input Frequency	50 to 60 Hz
Power (Rated) (Nom)	4.9 W
Lamp Current (Nom)	27 mA
Wattage Equivalent	50 W
Starting Time (Nom)	0.5 s
Warm Up Time To 60% Light (Nom)	0.5 s
Power Factor (Nom)	0.8
Voltage (Nom)	220-240 V


AV6063LK

Temperature		Product Data	Product Data		
T-Case Maximum (Nom)	80 °C	Full product code	AV6063WSAA		
Controls and Dimming					
Dimmable	Yes				
Approval and Application					
Suitable For Accent Lighting	Yes				
Energy Efficiency Label (EEL)	A+	Net Weight (Piece)	0.038 kg		
Energy Consumption kWh/1000 h	5 kWh				

Warnings and Safety

- Operating temperature range is between -20° C and 45° C ambient
- Only to apply in dry or damp locations and most of open fixtures with lamp-holders that offer sufficient space (10 mm free air space)
- Not intended for use with emergency light fixtures or exit lights


Dimensional drawing




Product	D	С
AV6063WSAA	50 mm	54 mm

GU10 230V5W-50W 355Im 36D 3000K GU10 Dim

Photometric data






MASTER LEDspotMV 35W GU10 930 36D 270Im


MASTER VALUE LEDspot MV

Photometric data




MASTER LEDspotMV 50W GU10 36D 355Im

Lifetime



MASTER LEDspotMV GU10 922-927 36D



MASTER LEDspotMV GU10 922-927 36D

