

# PROIETTORE STADIO IP66 DIMMERABILE 1-10V

## LED Samsung - Driver Invertronics



Vari **WATT**

85-265V

10°/30°/60°

Vari **LUMEN**

Samsung **LED**

IK08



CODICE	PARAMETRI BASE				PARAMETRI FOTOMETRICI						
	Misure	Watt	Input Volt	Finitura	CRI	Colore Luce	Lumen nominali	Ottica	Classe Erp EcoDesign	IP	
AV6610CSAA	765x510x136mm	750W	220-240V	Nero	■	5000K	15000LM	10°	B	IP66	
AV6611CSAA	765x510x136mm	750W	220-240V	Nero	■	5000K	15000LM	30°	B	IP66	
AV6612CSAA	765x510x136mm	750W	220-240V	Nero	■	5000K	15000LM	60°	B	IP66	
AV6613CSAA	965x510x136mm	1000W	220-240V	Nero	■	5000K	15000LM	10°	B	IP66	
AV6614CSAA	965x510x136mm	1000W	220-240V	Nero	■	5000K	15000LM	30°	B	IP66	
AV6615CSAA	965x510x136mm	1000W	220-240V	Nero	■	5000K	15000LM	60°	B	IP66	
AV6616CSAA	1165x510x136mm	1250W	220-240V	Nero	■	5000K	15000LM	10°	B	IP66	
AV6617CSAA	1165x510x136mm	1250W	220-240V	Nero	■	5000K	15000LM	30°	B	IP66	
AV6618CSAA	1165x510x136mm	1250W	220-240V	Nero	■	5000K	15000LM	60°	B	IP66	

