




STRIP LED 2835 9,6W/MT 24V SLIM 5/7MM



5 metri



CODICE	PARAMETRI BASE					PARAMETRI FOTOMETRICI					
	Misure	Unità di taglio	Input Volt	Watt nominali	Watt effettivi	CRI	Colore Luce	Lumen nominali	Lumen effettivi	Classe Erp EcoDesign	IP
AV7215NIAA	5000x5x1.5mm	7LED/50mm	24VDC	9.6W/m	-	≥90	4000K	1250LM/m	-	F	IP20
AV7213WIAA	5000x5x1.5mm	7LED/50mm	24VDC	9.6W/m	-	≥90	3000K	1250LM/m	-	F	IP20
AV7214WIAA	5000x5x1.5mm	7LED/50mm	24VDC	9.6W/m	-	≥90	2700K	1250LM/m	-	F	IP20
AV7354NIAA	5000x7x5mm	7LED/50mm	24VDC	9.6W/m	-	≥90	4000K	1250LM/m	-	F	IP67
AV7353WIAA	5000x7x5mm	7LED/50mm	24VDC	9.6W/m	-	≥90	3000K	1250LM/m	-	F	IP67

STRIP LED 2216 10W/MT 24V SLIM 3,5MM

5 metri



CODICE	PARAMETRI BASE					PARAMETRI FOTOMETRICI					
	Misure	Unità di Taglio	Input Volt	Watt nominali	Watt effettivi	CRI	Colore Luce	Lumen nominali	Lumen effettivi	Classe Erp EcoDesign	IP
AV2402CIAA	5000x3.5x1.5mm	7LED/50mm	24VDC	10W/m	9.2W/m	≥90	6000K	1000LM/m	980LM/m	F	IP20
AV2401NIAA	5000x3.5x1.5mm	7LED/50mm	24VDC	10W/m	9.2W/m	≥90	4000K	1000LM/m	940LM/m	F	IP20
AV2400WIAA	5000x3.5x1.5mm	7LED/50mm	24VDC	10W/m	9.2W/m	≥90	3000K	1000LM/m	890LM/m	F	IP20
AV5605WIAA	5000x3.5x1.5mm	7LED/50mm	24VDC	10W/m	9.2W/m	≥90	2700K	1000LM/m	890LM/m	F	IP20