

STRIP LED 5050 RGBW 19,2W/MT 24V

5 metri



24V

120°

720 Lm/mt

60 LED/mt

≥80

CODICE	PARAMETRI BASE				PARAMETRI FOTOMETRICI				
	Misure	Unità di taglio	Input Volt	Watt nominali	CRI	Colore Luce	Lumen nominali	Classe Erp EcoDesign	IP
AV2397XIAA	5000x12x2mm	6LED/100mm	24VDC	19,2W/m	≥80	RGB+6000K	720LM/m (solo bianco)	-	IP20
AV2396XIAA	5000x12x2mm	6LED/100mm	24VDC	19,2W/m	≥80	RGB+4000K	720LM/m (solo bianco)	-	IP20
AV2395XIAA	5000x12x2mm	6LED/100mm	24VDC	19,2W/m	≥80	RGB+3000K	720LM/m (solo bianco)	-	IP20
AV5083XIAA	5000x13x3mm	6LED/100mm	24VDC	19,2W/m	≥80	RGB+6000K	720LM/m (solo bianco)	-	IP65-TR
AV5082XIAA	5000x13x3mm	6LED/100mm	24VDC	19,2W/m	≥80	RGB+4000K	720LM/m (solo bianco)	-	IP65-TR
AV5081XIAA	5000x13x3mm	6LED/100mm	24VDC	19,2W/m	≥80	RGB+3000K	720LM/m (solo bianco)	-	IP65-TR
AV7142XIAA	5000x14x6mm	6LED/100mm	24VDC	19,2W/m	≥80	RGB+4000K	720LM/m (solo bianco)	-	IP67
AV7141XIAA	5000x14x6mm	6LED/100mm	24VDC	19,2W/m	≥80	RGB+3000K	720LM/m (solo bianco)	-	IP67

